

SHELBY SPECIALTY GLOVES

5002 & 5002F

February 2014

Specifications:

Outer Shell: Heavy 3 to 3.25 oz, popcorn and black color abrasion resistant, multidirectional fiber structure, brushed pigskin. Tanned hide does not contain PCP (pentachlorophenol), it's salts or esters.

4" Nomex wristlet, 5002F No Wristlet

Pattern: Gunn cut, keystone double layer thumb crotch protection. 1/8" wide, double row stitching around inset thumb.

Storage Attachment: Leather, 6mm x 51mm cut length, double stitched 38mm apart

Binding: Black 29mm Cotton (only model 5002F).

Wrist Shirring: 10mm Natural Elastic

Thread: Lock-Stitch sewn with kevlar thread, 8-10 stitches per inch. Spun Kevlar thread, tex 70,27.5 to 30.0/4 count, minimum break 12.0#

Origin: Made in U.S.A.
Meets NFPA 1977, 2011 Edition

Sizes: XS, S, M, L, XL, J

Design & Construction: Anatomically designed gunn cut, keystone glove and thumb pattern. The glove body shall extend 1" above the wrist crease & shall have shirred elastic snuggler. Glove shall have bound hem and machine washable. Meets NFPA 1977,2011 Edition

Shelby Specialty Gloves
3035 Centre Oak Way Suite 102
Germantown, TN. 38138
Phone: 800-888-3598 Fax: 901-362-9127 Email: sales@shelbyglove.com